

# OVERHEAD 590 LITRE

# MAINLINE

- Design Approval #: TNK0701
- Mainline Fabricator #: FAB0018
- Manufactured to AS1692-2006 Cat.2
- Tank design and fabricator approval registered with WorkSafe



Petrol or Diesel. Gravity Flow. No pump required. Compliant for farm and industry installations.

Available from 590 to 1950 Litre as a single or split fuel tank.

Tank is constructed from 3mm mild steel, sandblasted, coated with zinc primer and finished with a 2-pack epoxy undercoat and top coat. Standard colours – grey, white and cream. Other colours by request.

## MATERIALS

- TANK – 3mm Mild Steel
- LEGS – 40 x 40 x 5mm Angle
- STAYS – Flat Bar 25 x 5mm
- FOOTPLATES – 150 x 150 x 5mm

## STANDARD FITTINGS

- FILL and VENT – 50mm - Lockable
- DIPSTICK – Anodised Tee Section - Calibrated
- BALL VALVE – 25mm
- LOCKING COVER – Stainless Steel
- FILTER – NS10 Water Block
- HOSE – 25mm x 3 Metre Swaged Ends
- NOZZLE – Manual – 19 or 25mm
- NOZZLE HOLDER – Stainless Steel
- LADDER – 2 Sections
- BOLT BAG – Nuts, Bolts, Thread Tape, Instruction Sheet
- HAZCHEM LABELS – Petrol or Diesel
- MANUFACTURERS PLATE – Engraved with Compliance Information

## DIMENSIONS

- TANK – 1260mm x 770ø
- HEIGHT TO OUTLET – 1700mm
- OVERALL HEIGHT – 2600mm
- FOOTPRINT – 2200 x 2200mm
- CONCRETE PAD – 2400 x 2400 x 150mm thick
- FOOTINGS – 450 x 450 x 200mm at each leg
- TANK VOLUME – 590 Litres
- SAFE FILL LEVEL – 555 Litres

## OPTIONS

- FILTER UPGRADE – Piusi Water Captor
- LADDER UPGRADE – Platform Ladder incl. Handrails
- FLOW METERS – Piusi K33 Diesel or Petrol
- LOCK BOX – 2mm Galv. Steel Lockable Box
- PADLOCKS – Abus 83/45
- LADDER STEP – Clip on Step
- EXTRA HOSE – per metre