

# TRAILER TANK

## 1900 LITRE DIESEL

# MAINLINE

- Design Approval #: TAN09004
- Mainline Fabricator #: FAN0009
- Manufactured to Flammable liquids road tank wagons (Appendix D)
- Tank design and fabricator approval registered with WorkSafe



Mainline trailer tanks provide more options and flexibility in the way you use and store diesel. The convenience and time savings of fuel on site will add value to your business.

Pump options include Honda WB20 and 12 Volt.

Tank sandblasted and finished with 2-pack epoxy paint.

1600 and 1900 Litre trailers are tandem axle and braked units.

## MATERIALS

- TANK - 3mm Mild Steel
- TRAILER CHASSIS - Hot dip galvanised steel
- TRAILER BRAKES - CM Trailers

## STANDARD FITTINGS

- FILL PORT - 50mm
- VENT - 50mm Bayco Pressure Vent
- TOP SPILL BOX - Lockable
- DIPSTICK - Anodised T Section - Calibrated
- FILTER - Piusi Water Captor
- ANTI-SIPHON VALVE
- NOZZLE - Auto Shut Off
- TYRES & RIMS - 185 x 14/8 ply Tyres & 14" Galv. rims x 2
- JOCKEY WHEEL - Solid Rubber Tyre
- HAZCHEM LABELS - Diesel x 3
- MANUFACTURERS PLATE - Engraved with compliance information

## DIMENSIONS

- TANK BARREL - 1840 x 1140 ø
- TRAILER LENGTH - 3500mm
- TRAILER WIDTH - 1650mm
- OVERALL HEIGHT - 1600mm
- TANK VOLUME - 1880 Litres
- SAFE FILL LEVEL - 1785 Litres
- WEIGHT (empty) - 500kg

## OPTIONS

- FILTERS - NS10 Water Block, Piusi Water Captor filter, Donaldson Filtration
- HOSE REEL - 10 metre Retractable Hose & Reel (optional)
- PUMP OPTIONS - 12V Pump, Honda WB20