

ON GROUND 950 LITRE - DIESEL

MAINLINE

- Design Approval #: TNK0710
- Mainline Fabricator #: FAB0018
- Manufactured to AS1692-2006 Cat.2
- Tank design and fabricator approval registered with WorkSafe

On Ground tanks are approved for petrol and diesel and typically fitted with a pump. Compliant for farm and industry installations including connection to boilers, burners and generators. Available as 590, 950, 1400 and 1950 Litre as single compartment or split fuel tank. Tank is constructed from 3mm mild steel, sandblasted, coated with zinc primer and finished with a 2-pack epoxy undercoat and top coat. Standard colours – grey, white or cream. Other colours by request.



MATERIALS

- TANK – 3mm Mild Steel
- LEGS – 75 x 75 x 3mm
- FOOTPLATES – 200 x 200 x 5mm

STANDARD FITTINGS

- FILL and VENT – 50mm - Lockable
- DIPSTICK – Anodised Tee Section - Calibrated
- HAZCHEM LABELS – Petrol or Diesel
- MANUFACTURERS PLATE – Engraved with Compliance Information

DIMENSIONS

- TANK – 1260mm x 1000ø
- HEIGHT TO OUTLET – 1200mm
- OVERALL HEIGHT – 1250mm
- FOOTPRINT – 1240 x 1295mm
- CONCRETE PAD – 1400 x 1200 x 150mm thick
- TANK VOLUME – 986 Litres o/a
- SAFE FILL LEVEL – 935 Litres o/a

OPTIONS

- FILTER OPTIONS – NS10 Water block, Piusi Water Captor
- PUMP OPTIONS – Petrol – Fillrite rotary hand pump, Piusi EX50 12V or 230V
- PUMP OPTIONS - Diesel – Fillrite rotary hand pump, 12 Volt, 230 Volt, Honda petrol powered