


OVERHEAD 1400 LITRE

MAINLINE

- Design Approval #: TNK0704
- Mainline Fabricator #: FAB0018
- Manufactured to AS1692-2006 Cat.2
- Tank design and fabricator approval registered with WorkSafe

Petrol or Diesel. Gravity Flow. No pump required.
Compliant for farm and industry installations.
Available from 590 to 1950 Litre as a single or split fuel tank.
Tank is constructed from 3mm mild steel, sandblasted, coated with zinc primer and finished with a 2-pack epoxy undercoat and top coat.
Standard colours – grey, white or cream. Other colours by request.



MATERIALS

- TANK – 3mm Mild Steel
- LEGS – 50 x 50 x 8mm Angle
- STAYS – Flat Bar 25 x 5mm
- FOOTPLATES – 150 x 150 x 5mm

STANDARD FITTINGS

- FILL and VENT – 50mm - Lockable
- DIPSTICK – Anodised Tee Section - Calibrated
- BALL VALVE – 25mm
- LOCKING COVER – Stainless Steel
- FILTER – NS10 Water Block
- HOSE – 25mm x 3 Metre Swaged Ends
- NOZZLE – Manual – 19 or 25mm
- NOZZLE HOLDER – Stainless Steel
- LADDER – 2 Sections
- BOLT BAG – Nuts, Bolts, Thread Tape, Instruction Sheet
- HAZCHEM LABELS – Petrol or Diesel
- MANUFACTURERS PLATE – Engraved with Compliance Information

DIMENSIONS

- TANK – 1560mm x 1070ø
- HEIGHT TO OUTLET – 1700mm
- OVERALL HEIGHT – 2900mm
- FOOTPRINT – 2200 x 2400mm
- CONCRETE PAD – 2600 x 2600 x 150mm thick
- FOOTINGS – 600 x 600 x 300mm at each leg
- TANK VOLUME – 1420 Litres
- SAFE FILL LEVEL – 1350 Litres

OPTIONS

- FILTER UPGRADE – Piusi Water Captor
- LADDER UPGRADE – Platform Ladder incl. Handrails
- FLOW METERS – Piusi K33 Diesel or Petrol
- LOCK BOX – 2mm Galv. Steel Lockable Box
- PADLOCKS – Abus 83/45
- LADDER STEP – Clip on Step
- EXTRA HOSE – per metre