

DOUBLE SKIN

4650 LITRE – DIESEL ONLY

MAINLINE

- Design Approval #: TNK1012
- Mainline Fabricator #: FAB0018
- Manufactured to AS1692-2006 Cat.4
- Tank design and fabricator approval registered with WorkSafe

Mainline double skin tanks are a primary tank within an outer tank. This double skin forms the secondary containment. The space between the inner and outer tank is the interstitial space.

Our double skin tanks have certification to be connected to boilers, burners and generators or fitted with a variety of pump options to suit your needs.

Mainline double skin tanks are New Zealand made and comply with secondary containment regulations.



MATERIALS

- TANK - Inner & Outer Skin - 5mm Mild Steel
- LEGS - 100 x 100 x 4mm
- FOOTPLATES - 350 x 350 x 12mm

STANDARD FITTINGS

- FILL and VENT – 50mm
- TOP SPILL BOX – 15 Litre – Lockable
- INTERSTITIAL VENT – 25mm
- INTERSTITIAL PORT – 40mm
- HAZCHEM LABELS – Diesel
- CALIBRATED DIPSTICK
- MANUFACTURERS PLATE - Engraved with compliance information

DIMENSIONS

- TANK - Outer Skin - 1800mm x 1900mm Ø
- HEIGHT TO OUTLET - 2050mm
- OVERALL HEIGHT - 2200mm
- FOOTPRINT - 1830 x 1950mm
- CONCRETE PAD - 2500 x 2500 x 150mm with SE72 mesh
- TANK VOLUME - 4720 Litres
- SAFE FILL LEVEL - 4484 Litres

OPTIONS

- FILTER OPTIONS - NS10 Water block - Piusi Water Captor - Donaldson Filtration
- PUMP OPTIONS - Fillrite rotary hand pump - Electric (12V or 230V) - Honda petrol powered
- MANAGEMENT SYSTEMS – Piusi MC70 software & keys, Piusi Cube70 B.Smart, Everlink