

UTE TANKS

250 / 300 / 400 LITRE DIESEL

MAINLINE

- Design Approval #: n/a
- Mainline Fabricator #: FAN0009
- Manufactured to Flammable liquids road tank wagons code



Mainline Ute Tanks are for **Diesel only (3.1D)**. Manufactured from 4mm aluminium and Built to Last. Standard units are available in 250, 300 and 400 Litre units. These are fitted with a 12 Volt pump system which can be connected to a battery or wired into a vehicle. Custom units can be designed and manufactured to suit your requirements. **PETROL (3.1A) cannot be carried on New Zealand roads** in a ute tank unless the tank has a certification number (TAN#) issued by WorkSafe.

MATERIALS

- TANK – 4mm Aluminium - 5052

STANDARD FITTINGS

- FILL – 50mm Camlock
- VENT – Bayco Pressure Vent
- HAZCHEM LABEL – Diesel (3Z)
- MANUFACTURERS PLATE – Engraved with compliance information

DIMENSIONS

- **250 LITRE TANK** – 1000 x 600 x 450mm High
- TANK VOLUME – 270 Litres – SFL – 256 Litres
- **300 LITRE TANK** – 1200 x 600 x 450mm High
- TANK VOLUME – 324 Litres – SFL – 307 Litres
- **400 LITRE TANK** - 1500 x 600 x 450mm High
- TANK VOLUME – 405 Litres – SFL – 384 Litres

PUMP SET UP

- PUMP – Piusi Carry 3000 12 Volt
- FILTER – Piusi Water Captor
- PUMP BOX LID – 450 x 400 x 185mm High - Lockable
- FUEL HOSE – 25mm x 4 metres (swaged ends)
- NOZZLE – Piusi A60 Auto shut off (incl. nozzle holder)